

Muuntoyhde


RCU



Tuotekuvaus

Syvävedetty keskeismuuntoyhde. Virtausteknisesti optimoitu muotoilu takaa matalan painehäviön. Ød sopii kanavan sisään.

Mitat



Ød ₁ nom	Ød ₂ nom	l [mm]	Tyyppi	m kg
80	63	18	1	0,12
100	63	30	1	0,17
100	80	26	2	0,18
125	80	36	2	0,16
125	100	27	2	0,21
160	80	55	1	0,31
160	100	46	2	0,23
160	125	35	2	0,22
200	100	46	2	0,22
200	125	55	2	0,30
200	160	39	2	0,29
250	125	70	1	0,62
250	160	60	2	0,46
250	200	42	2	0,46
315	160	91	1	0,86
315	200	74	1	0,72
315	250	50	1	0,74
400	200	118	1	1,37
400	250	94	1	1,38
400	315	54	1	1,29
500 *	250	128	1	2,30
500	315	95	1	1,90
500	400	68	1	1,76
630 *	315	160	1	3,37
630 *	400	118	1	3,17
630 *	500	68	1	2,89

* Pyöristetyllä liitoksella

Tilausesimerkki

Tuotetunnus	RCU	315	250
Mitta Ød ₁			
Mitta Ød ₂			





Muuntoyhde



RCU

Tekniset tiedot

1 dimensiojako



2 dimensiojaot



3 dimensiojaot

